

Biometric Access & Time Attendance System: Model AFA210



Technical Specification

- User Capacity: 1500 fingerprints, standalone storage 50000 records
- Algorithm version : vx9.0
- Identification : 1:1 or 1:N, fingerprint only, ID number+fingerprint, ID number+ code, card+fingerprint
- Fingerprint parameter : Identification time<=2s, FAR<=0.0001%,FRR<=1%
- Access control function : 50 time zones, 5 groups, 10 open door combination, support multi-users enter, 10A/12VDC relay switching value or output voltage
- Alarm function : Can give alarm when destroying it, illegally open door, threatened by hijackers, and output touch off alarm signals, circumscribed alarm, alarm lamp, alarm lamp or alarm host computer, Wiegand In and Wiegand Out.
- Hardware: AFA210.
- Communications : TCP/IP or RS 232/485
- Function keys: 4 function keys.
- Display, voice and keyboard : Four lines blue LCD, double color LED indicator light, multi-language
- Power supply parameter : 12V DC, watchful waiting current<50 mA, working current<400mA
- Sensor : Optical sensor
- Operating environment : Temperature 0℃-45℃; humidity 20%-80%
- Language: Multi-language version
- U disk : 128M
- Size: 150 x 145 x 40 mm
- Standard: Webserver, Wireless Doorbell, Short message
- Optional: ID/HID/Mifare card, Workcode, WIFI, GPRS, RIS, Antipass-back